

LIGHT MODULES

REF	DESCRIPTION	Installation length L1 (mm)	Weight (Kg)	W
09.8000.DD**	DIVERSION DOWN 1000 2700K CRI90	1000	0,6	13
09.8001.DD**	DIVERSION DOWN 1000 3000K CRI90	1000	0,6	13
09.8002.DD**	DIVERSION DOWN 1500 2700K CRI90	1500	0,9	20
09.8003.DD**	DIVERSION DOWN 1500 3000K CRI90	1500	0,9	20
09.8004.DD**	DIVERSION DOWN 2000 2700K CRI90	2000	1,2	27
09.8005.DD**	DIVERSION DOWN 2000 3000K CRI90	2000	1,2	27
09.8006.DD**	DIVERSION DOWN 2500 2700K CRI90	2500	1,5	34
09.8007.DD**	DIVERSION DOWN 2500 3000K CRI90	2500	1,5	34
09.8010.DD**	DIVERSION UP&DOWN 1000 2700K CRI90	1000	0,6	20
09.8011.DD**	DIVERSION UP&DOWN 1000 3000K CRI90	1000	0,6	20
09.8012.DD**	DIVERSION UP&DOWN 1500 2700K CRI90	1500	0,9	31
09.8013.DD**	DIVERSION UP&DOWN 1500 3000K CRI90	1500	0,9	31
09.8014.DD**	DIVERSION UP&DOWN 2000 2700K CRI90	2000	1,2	43
09.8015.DD**	DIVERSION UP&DOWN 2000 3000K CRI90	2000	1,2	43
09.8016.DD**	DIVERSION UP&DOWN 2500 2700K CRI90	2500	1,5	54
09.8017.DD**	DIVERSION UP&DOWN 2500 3000K CRI90	2500	1,5	54
09.8020.DD**	DIVERSION DOWN SPOTS 1000 2700K CRI90	1000	0,6	13+Spots*
09.8021.DD**	DIVERSION DOWN SPOTS 1000 3000K CRI90	1000	0,6	13+Spots*
09.8022.DD**	DIVERSION DOWN SPOTS 1500 2700K CRI90	1500	0,9	20+Spots*
09.8023.DD**	DIVERSION DOWN SPOTS 1500 3000K CRI90	1500	0,9	20+Spots*
09.8024.DD**	DIVERSION DOWN SPOTS 2000 2700K CRI90	2000	1,2	27+Spots*
09.8025.DD**	DIVERSION DOWN SPOTS 2000 3000K CRI90	2000	1,2	27+Spots*
09.8026.DD**	DIVERSION DOWN SPOTS 2500 2700K CRI90	2500	1,5	34+Spots*
09.8027.DD**	DIVERSION DOWN SPOTS 2500 3000K CRI90	2500	1,5	34+Spots*
09.8030.DD**	DIVERSION UP&DOWN 1000 2700K CRI90	1000	0,6	20+Spots*
09.8031.DD**	DIVERSION UP&DOWN SPOTS 1000 3000K CRI90	1000	0,6	20+Spots*
09.8032.DD**	DIVERSION UP&DOWN SPOTS 1500 2700K CRI90	1500	0,9	31+Spots*
09.8033.DD**	DIVERSION UP&DOWN SPOTS 1500 3000K CRI90	1500	0,9	31+Spots*
09.8034.DD**	DIVERSION UP&DOWN SPOTS 2000 2700K CRI90	2000	1,2	43+Spots*
09.8035.DD**	DIVERSION UP&DOWN SPOTS 2000 3000K CRI90	2000	1,2	43+Spots*
09.8036.DD**	DIVERSION UP&DOWN SPOTS 2500 2700K CRI90	2500	1,5	54+Spots*
09.8037.DD**	DIVERSION UP&DOWN SPOTS 2500 3000K CRI90	2500	1,5	54+Spots*

* Max. 2 Spots / Profile. (Spots not included). To be order separately.

** DD = FINISH. CZ = Bronze / 1A = Anodic Ice / 14 = Black / 40 = White

DRIVERS (Note: Not for US, see pec sheet)

REF	DESCRIPTION
60.9426	ALIMT.LED 24V-120W DALI 90-305V PWM-120-24DA-OL
60.9416	ALIMT.LED 24V-120W 0/1-10V 90-305V PWM-120-24
60.9392	CBU-ASD Control Unit (CASAMBI for 60.9416)
60.9361	DRIVER IDLV-65-24 180-295V 24V 57W DIM 0-1
⚠ Broadcast control System.	

SPOTS

REF	DESCRIPTION	W
09.383X.DD	ATOM 90	5,5
09.384X.DD	ATOM 120	8


SUSPENSION ACCESORIES

REF	DESCRIPTION
06.5300.DD	DIVERSION FEED SUSP.JOINT RECESSED
06.5301.DD	DIVERSION SUSP. JOINT RECESSED
06.5302.DD	DIVERSION FEED SUSP.JOINT RECESSED ROSE
06.5303.DD	DIVERSION SUSP. JOINT SURFACE

SURFACE ACCESORIES




REF	DESCRIPTION
06.5304.DD	DIVERSION FEED JOINT RECESSED
06.5305.DD	DIVERSION JOINT RECESSED/CONCRETE
06.5306.DD	DIVERSION FEED JOINT RECESSED ROSE

ASSEMBLING JOINING / RECOMMENDED FEED PROFILE CONNECTION




A LUMINAIRE INSTALLATION





INSTALACIÓN DE LA LUMINARIA / INSTALLAZIONE DELLA LAMPADA /
INSTALLATION DER BELEUCHTUNG / INSTALLATION DU LUMINAIRE /
INSTALAÇÃO DO APARELHO DE ILUMINAÇÃO / 照明器具の設置・据付け /
灯具的安装 / МОНТАЖ ОСВЕТИТЕЛЬНОГО ПРИБОРА
ШАМДАЛДЫ ОРНАТУ / تركيب وحدة الإنارة







UP LIGHT



BALL JOINT PROFILE INSTALLATION




ATOM 90 / 120




PROFILE	L2
1000 mm	287 mm
1500 mm	287 mm
2000 mm	457 mm
2500 mm	457 mm


⚠ Minimum angle between modules




ALIMT.LED 24V-120W DALI 90-305V PWM-120-24DA-OL (60 .9426) (Not for US)




ALIMT.LED 24V-120W 0/1-10V 90-305V PWM-120-24 (60.9416) (Not for US)



CBU-ASD Control Unit (CASAMBI for 60.9416) (60.9392 + 60.9416) (Not for US)



DRIVER IDLV-65-24 180-295V 24V 57W DIM 0-1 (60.9361)



DIMENSION CONVERSION TABLE

m	inch
	157,48

mm	inch
16	0,62
34	1,33
287	11,29
457	17,99
1000	39,37
1500	59,05
2000	78,74
250	98,42

US ONLY

