








WARNING/ADVERTENCIA
Only ceiling Installation /Solo instalación en techo





A.3 FIND ME 0 / FIND ME 1 / FIND ME 2











**WARNING FOR "FINDME 2"/
ADVERTENCIA PARA "FINDME 2"**
Only ceiling Installation /Solo instalación en techo.






A.4 FIND ME 1 SUSPENSION



CABLE ADJUSTMENT




A.5 STOPPER (08.0630.XX)




B LUMINAIRE TILT ADJUSTMENT

REGULACIÓN DE LA INCLINACIÓN DE LA LUMINARIA / REGOLAZIONE DELL'INCLINAZIONE DEL DISPOSITIVO DI ILLUMINAZIONE / NEIGUNGSREGLER DER LICHTQUELLE / RÉGLAGE DE L'INCLINAISON DU LUMINAIRE / REGULAÇÃO DA INCLINAÇÃO DA LUMINÁRIA / 照明の角度調節 / 调节照明的倾斜度 / РЕГУЛИРОВКА НАКЛОНА ОСВЕТИТЕЛЬНОГО ПРИБОРА / ШАМДАЛДЫ ЁЖКЕЙТУДИ РЕТТЕУ ضبط إمالة المصباح


B.1 FIND ME 0 / FIND ME 1 / FIND ME 2




B.2 ATOM 90 / 120



B.3 ATOM 200



WARNING/ADVERTENCIA
Only install out of the volume of accessibility.
Solo instale fuera del volumen de accesibilidad.



LED DRIVER ≤ 60 Vout

ATTENTION

The voltage under load does not exceed 25 V r.m.s. or 60 V ripple-free d.c. and the no-load voltage does not exceed 35 V peak or 60 V ripple-free d.c.
El voltaje bajo carga no excede los 25 V r.m.s. o 60 V sin ondulaciones d.c. y el voltaje sin carga no supera los 35 V pico o 60 V sin ondulaciones d.c.

WARNING




E La luminaria debería colocarse de forma que no se espera una mirada prolongada a la luminaria a una distancia más cercana a D m
GB The luminaire should be positioned so that prolonged staring into the luminaire at a distance of D m. is not expected.
I L'apparecchio dovrà essere collocato in modo che non ci si aspetti uno sguardo prolungato verso l'apparecchio da una distanza di circa D m.
D Die Lampe ist so zu positionieren, dass ein direkter Blick vermieden wird. Dies geschieht durch eine Längspositionierung auf D Metern Distanz.
F Le luminaire doit être positionné de manière à ne pas attendre un regard prolongé vers le luminaire à une distance proche de D mètres.
P A luminária deverá ser posicionada de tal forma que uma pessoa a D metros de distancia não mantenha o olhar prolongado à mesma..
JP 本照明器具は D mより近い距離から内部を長時間凝視することがない場所に設置してください。
CN 请勿将灯具放置于接近于离视线 D 公尺的距离。 .

RU Светильник должен располагаться таким образом, чтобы длительное смотрение на светильник находилось на расстоянии x м	
AR متر X لتجنب انظر الى الإنارة لمدة طويلة، يجب وضع الإنارة على مسافة أقرب من	
KZ Ұзақ қарау күтілместей а x m-ға ең жақын дейінгі қашықтықтағы жарық түсіргіш құрылғы оранлыстырған жөн	
Ref.	
09.384X	D = 1,8 M
09.386X	D = 2,6 M




C ACCESSORIES

ACCESORIOS / ACCESSORI / ZUBEHÖR / ACCESSOIRES / ACCESSÓRIOS / アクセサリー / 配件 / АКЦЕССУАРИ / КЕРЕК-ЖАРАҒАТAP / إكسسوارات

FIND ME 1 / FIND ME 2 / FIND ME 1 SUSPENSION / ATOM 120



FIND ME 0 / ATOM 90



DIMENSION CONVERSION TABLE

m	inch
1,25	49,21
1,8	70,86
2,5	98,43

CASAMBI VERSION

- The CASAMBI control will be 1% to 100%
- MAX. 200 luminaires for a single CASAMBI network.
- MAX. 15 meters between luminaires if the environment is an open space (no wall in between luminaires)
- To know more about all CASAMBI options visit www.casambi.com