

FLOS

06.1610.40 White

90° Corner. Can be powered

Designed by FLOS Architectural, 2015



Length: 150 - Wall surface, Ceiling surface

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Wall surface, Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	White
Trim	No
Length (mm)	150
Net weight (kg)	0.76
IP internal	20
IP external	20



Download

Mounting instructions



Electrical

Forward voltage (V) 24

Accessories & Power Supply



OPTIONAL
Installation

08.8887.40A
Endcap. 2 unit kit



OPTIONAL
Power supply
Electrical

60.9352
LED power supply source for remote installation in 24V/200W electric control panel. To avoid problems of overload it is recommended to install a power source every 185W. 100/240V.



OPTIONAL
Power supply
Electrical

60.9089
Electronic transformer with constant voltage (24V) for LED. 100/240V. 60W



OPTIONAL
Power supply
Electrical

60.9407
Electronic transformer with constant voltage (24V) for LED. 100/240V. 120W



OPTIONAL
Control interface
Electrical

60.9678A
LED module Dali/Push dimmable control unit for 12, 24 or 48Vdc