

FLOS

FA53000856.A Matte Stainless Steel


A-Rise 130

Designed by FLOS Outdoor, 2012



4W - 189lm - 3000K - CRI> 80 - Beam° 120

Mains voltage LED light source included. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 250 mm cable with an integrated 2-way, 3-pole H2O STOP connection system guaranteeing the water tightness of the connection. Frosted glass.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

| | |
|------------------------|---------------|
| EAN | 8054793649825 |
| Mounting | In-ground |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 4 |
| System power (W) | 4 |
| Source flux (lm) | 380 |
| Lumen Output (lm) | 189 |

Physical

| | |
|---------------------|-----------------------|
| Colour | Matte Stainless Steel |
| Orientation | Fixed |
| Net weight (kg) | 0.53 |
| Package height (mm) | 175 |
| Package width (mm) | 135 |
| Package length (mm) | 135 |
| IP internal | 67 |
| IP external | 66 |

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP




Ecodesign and Energy Labelling



Non-replaceable light source

Schematic light drawing



Beam Angle: 120°

| h(m) | E(lx) | D(m) |
|------|-------|-------|
| 1 | 51 | 3.49 |
| 2 | 13 | 6.98 |
| 3 | 6 | 10.48 |
| 4 | 3 | 13.97 |
| 5 | 2 | 17.46 |

Luminous flux luminaire
189 lm

Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 80 |
| Beam angle C0-180 (°) | 120 |
| Beam angle C90-270 (°) | 120 |
| Extreme cut off | No |

Electrical

| | |
|--------------------|--------------|
| Insulation class | I |
| Frequency (Hz) | 50/60 |
| Main voltage (Vac) | 220-230 |
| Power supply | Integrated |
| Dimmable | No |
| Power supply type | Non Dimmable |
| Dimming interface | Not Dimmable |
| Emergency | No |

Accessories & Power Supply



REQUIRED Accessory

FA50

Box for Installation A-Rise 130



OPTIONAL Accessory

F990C010000

3/4 way terminal block 4 poles
IP68 H2O stop. (ø5,5÷12mm
cable)



OPTIONAL Accessory

F990E00A000

S.P.D. (SURGE PROTECTION
DEVICE)