

# FLOS

08.8572.14DDA Black

## Accent Lighting 3000K. Set of 12 spots for circle of light. Dimmable DALI



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
System power (W)	54
Source flux (lm)	3780
Lumen Output (lm)	2417

### Physical

Colour	Black
Trim	No
Recessed depth (mm)	150
Net weight (kg)	3.64
IP internal	20

### Download

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ LDT](#)


### Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional



### Schematic light drawing



## Photometric

Light distribution	Symmetric
CCT (K)	3000
Beam angle C0-180 (°)	12
Extreme cut off	Yes
UGR <sub>L</sub>	<10

## Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
LED current (mA)	1050
Dimmable	Yes
Dimming interface	Remote Dimmable (Dimmer Not Included)

## Notes

Junction box, power supply and cables included.

---