

# FLOS

03.6274.40BCB White

## Anthony Spot Track Casambi integrated


Designed by Antonio Citterio, 2020



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	14
Source flux (lm)	1308
Lumen Output (lm)	1060

### Physical

Colour	White
Net weight (kg)	0.5
IP internal	20

### Download

[Mounting instructions](#)  PDF

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	15
UGR <sub>L</sub>	<10

## Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	900
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable Casambi
Dimming interface	Remote Dimmable (Dimmer Not Included)

## Notes

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® by Casambi.

## Accessories & Power Supply



OPTIONAL  
Accessory

Optical

08.0050.00

Flood lens



OPTIONAL  
Accessory

Optical

08.8418.68A

Elliptical lens



OPTIONAL  
Accessory

Optical

08.8419.14A

Honeycomb