

Anthony Spot Track Dali Version

Designed by Antonio Citterio, 2018



LED - LED array - 1479lm - Beam° 15

Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Lamp category          | LED                 |
| Number of lamps        | 1                   |
| System power (W)       | 17.5                |
| Source flux (lm)       | 1931                |
| Lumen Output (lm)      | 1479                |
| Efficacy (lm/W)        | 85                  |

### Physical

|                          |            |
|--------------------------|------------|
| Colour                   | Black      |
| Trim                     | No         |
| Orientation              | Adjustable |
| Rotation (°)             | 360        |
| Longitudinal tilting (°) | 90         |
| Spot diameter (mm)       | 110        |
| Length (mm)              | 178        |
| Net weight (kg)          | 0.43       |
| IP internal              | 20         |
| IP external              | 20         |



### Download

Mounting instructions [Download PDF](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings

2D [Download ZIP](#)  
3D [Download ZIP](#)




### Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Schematic light drawing



Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Direct                        |
| Light distribution       | Symmetric                     |
| LED Life / Failure Ratio | L80B50 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 15                            |
| Beam angle C90-270 (°)   | 15                            |
| Extreme cut off          | No                            |
| UGRL                     | <16                           |

Electrical

|                     |                                          |
|---------------------|------------------------------------------|
| Insulation class    | III                                      |
| Forward voltage (V) | 48                                       |
| LED current (mA)    | 450                                      |
| Power supply        | Remote excluded                          |
| Dimmable            | Yes                                      |
| Power supply type   | Dimmable DALI 2                          |
| Dimming range (%)   | 20-100                                   |
| Dimming interface   | Remote Dimmable<br>(Dimmer Not Included) |
| Emergency           | No                                       |

Notes

Only compatible with DALI profile version. For wireless lighting control, choose integrated Casambi versions.

Accessories & Power Supply



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8419.14A

Honeycomb



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.0050.00

Flood lens



OPTIONAL  
Accessory

ACCESSORYTYPE4

08.8418.68A

Elliptical lens