


Anthony Spot Track Dali Version

Designed by Antonio Citterio, 2018



LED - LED array - 1480lm - Beam° 28

Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	17.5
Source flux (lm)	1931
Lumen Output (lm)	1480
Efficacy (lm/W)	85

Physical

Colour	Polished Silver
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Spot diameter (mm)	110
Length (mm)	178
Net weight (kg)	0.43
IP internal	20



Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)




Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	28
Beam angle C90-270 (°)	28
Extreme cut off	No
UGRL	<16

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	450
Power supply	Remote excluded
Dimmable	Yes
Power supply type	Dimmable DALI 2
Dimming range (%)	20-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency	No

Notes

Only compatible with DALI profile version. For wireless lighting control, choose integrated Casambi versions.

Accessories & Power Supply



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8419.14A

Honeycomb



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0050.00

Flood lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8418.68A

Elliptical lens