

03.8028.40B1V White

Anthony Spot Track Dimmable 1-10V

Designed by Antonio Citterio, 2018



LED - LED array - 1480lm - Beam° 28

Accent lighting LED module to be installed in The Tracking Magnet System. To obtain flood optics (35°) order Anthony Spot Medium + flood lens.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	17.5
Source flux (lm)	1931
System flux (lm)	1480
Efficacy (lm/W)	85

Physical

Color	White
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (in)	7
Net weight (lb)	0.95
IP internal	20
IP external	20



Download

- [Family spec sheet](#)  ZIP
- [Mounting instructions](#)  PDF

Photometric Files


- [LDT / IES](#)  ZIP

Technical Drawings

- [2D](#)  ZIP
- [3D](#)  ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	28
Beam angle C90-270 (°)	28
Extreme cut off	No
UGRL	<16

Electrical

Insulation class	III
Forward voltage (V)	48
LED current (mA)	450
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming range (%)	20-100
Dimming interface	Remote Dimmable (Dimmer Not Included)
Emergency type	No

Notes

Only compatible with 1-10V profile version. For wireless lighting control, choose integrated Casambi versions.

Accessories & Power Supply



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8419.14A

Honeycomb



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0050.00

Flood lens



OPTIONAL
Accessory

ACCESSORYTYPE4

08.8418.68A

Elliptical lens