

# FLOS

03.6278.40B White

## Anthony Spot Track On Board Dimmer


Designed by Antonio Citterio, 2017



Accent lighting LED module to be installed in The Running Magnet System. Built-in DC/DC electronic voltage converter.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Track               |
| Environments           | Indoor dry location |
| Light source type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Number of lamps        | 1                   |
| Power (W)              | 14                  |
| Source flux (lm)       | 1045                |
| Lumen Output (lm)      | 870                 |

### Physical

|                 |       |
|-----------------|-------|
| Colour          | White |
| Net weight (kg) | 0.5   |
| IP internal     | 20    |

### Download

[Mounting instructions](#) PDF

### Photometric Files

[LDT / IES](#) ZIP

### Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP




## Schematic light drawing



## Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional

## Photometric

|                       |           |
|-----------------------|-----------|
| Lighting type         | Direct    |
| Light distribution    | Symmetric |
| CCT (K)               | 2700      |
| CRI>                  | 90        |
| Beam angle C0-180 (°) | 22        |
| Extreme cut off       | No        |
| UGR <sub>L</sub>      | <10       |

## Electrical

|                     |                   |
|---------------------|-------------------|
| Insulation class    | III               |
| Forward voltage (V) | 24                |
| LED current (mA)    | 900               |
| Power supply        | Remote excluded   |
| Dimmable            | Yes               |
| Power supply type   | Dimmer on board   |
| Dimming interface   | Dimmer Integrated |

## Notes

Maximum 9 spots for a single driver. To obtain flood optics (35°) order Anthony Spot Medium + flood lens. For wireless lighting control, choose integrated Casambi versions.

## Accessories & Power Supply



OPTIONAL  
Accessory

Optical

08.0050.00

Flood lens



OPTIONAL  
Accessory

Optical

08.8418.68A

Elliptical lens



OPTIONAL  
Accessory

Optical

08.8419.14A

Honeycomb