

# FLOS


09.3851.CZ Bronze

## Atom 200

Designed by Piero Lissoni, 2018

10.5W - 395lm - 2700K - CRI> 90 - Beam° 110

General lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module non-dimmable. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1005
System flux (lm)	395
Efficacy (lm/W)	38

### Physical

Color	Bronze
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (in)	7.56
Net weight (lb)	1.04
IP internal	20

### Download

Family spec sheet	<a href="#">↓ ZIP</a>
Mounting instructions	<a href="#">↓ PDF</a>
Item information	<a href="#">↓ JPG</a>

### Photometric Files


LDT / IES	<a href="#">↓ ZIP</a>
-----------	-----------------------

### Technical Drawings

2D	<a href="#">↓ ZIP</a>
3D	<a href="#">↓ ZIP</a>



## Schematic light drawing



## Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

## Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	420
Driver	Remote excluded
Dimmable	Yes
Dimming type	Non Dimmable

## Ecodesign and Energy

### Labelling

