

Atom 200 1-10V Dimmable


Designed by FLOS Architectural, 2023

10.5W - 395lm - 2700K - CRI> 90 - Beam° 110

LED general lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual control via DALI protocol and broadcast mode via 1-10V.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1005
System flux (lm)	395
Efficacy (lm/W)	38

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20

Download

- Family spec sheetZIP
- Mounting instructionsPDF

Photometric Files


- LDT / IESZIP

Technical Drawings

- 2DZIP
- 3DZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	650
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming range (%)	1-100
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional