

FLOS

09.3950.40 White

Atom 200 Casambi integrated


Designed by Piero Lissoni, 2020



General lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 0/1-10V DALI or Casambi driver in broadcast mode. Dimmer not included. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Track |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Number of lamps | 1 |
| Power (W) | 10.5 |
| Source flux (lm) | 1079 |
| Lumen Output (lm) | 424 |
| Efficacy (lm/W) | 41 |

Physical

| | |
|--------------------------|------------|
| Colour | White |
| Trim | No |
| Orientation | Adjustable |
| Rotation (°) | 360 |
| Longitudinal tilting (°) | 90 |
| Spot diameter (mm) | 192 |
| Net weight (kg) | 0.47 |
| IP internal | 20 |

Download

[Mounting instructions](#) PDF

[Item information](#) JPG

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Photometric

| | |
|--------------------------|--------------------------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| McAdam steps (SDCM) | 3 |
| LED Life / Failure Ratio | L80B50>50.000h (Tc=85°C) |
| Beam angle C0-180 (°) | 110 |
| Beam angle C90-270 (°) | 110 |
| Extreme cut off | No |

Electrical

| | |
|---------------------|------------------|
| Insulation class | III |
| Forward voltage (V) | 24 |
| LED current (mA) | 420 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Power supply type | Dimmable Casambi |
| Dimming range (%) | 1-100 |

Ecodesign and Energy

Labelling



Notes

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.