

FLOS

09.3951.14 Black

Atom 200 Casambi integrated


Designed by Piero Lissoni, 2020



General lighting LED module to be installed in the Zero Track system. Incorporated DC/DC electronic converter. Module regulated via 0/1-10V DALI or Casambi driver in broadcast mode. Dimmer not included. To individually control the lights, select integrated Casambi versions. Not suitable for vertical installations.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1005
System flux (lm)	395
Efficacy (lm/W)	38

Physical

Color	Black
Trim	No
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
Length (in)	7.56
Net weight (lb)	1.04
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF
Item information	JPG

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy
Labelling

Replaceable (LED only)
light source by a
professional

Replaceable control
gear by a professional

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	420
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable Casambi
Dimming range (%)	1-100

Notes

The control system with the Casambi version of light fixtures is directly and individually regulated wirelessly using the application FLOS Control® powered by Casambi.