

Atom 200 Non Dimmable

Designed by FLOS Architectural, 2023

10.5W - 424lm - 3000K - CRI> 90 - Beam° 110

LED general lighting module for installation in the Zero Track Pro system. Electronic DC/DC converter incorporated. Individual wireless adjustment via Casambi. Casambi control implemented via the FLOS Control® app for mobile devices (available in the Apple Store and Google Play).

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Track
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	10.5
Source flux (lm)	1080
System flux (lm)	424

Physical

Color	Brushed Bronze
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	90
IP internal	20



Download

Family spec sheet [ZIP](#)
Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)


Technical Drawings

2D [ZIP](#)
3D [ZIP](#)




Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	24
LED current (mA)	420
Driver	Remote excluded
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)