

FLOS



F003B31BU12 Forest Green

Bellhop Bollard H 850 mm Dimmable 1-10V


Designed by Edward Barber and Jay Osgerby, 2018

8W - 580lm - 3000K - CRI> 80

100-240V power supply included. Ready for installation on solid surface. Each luminaire is equipped with 200 mm cable for connection inside the luminaire body. Recommended connection with a 2 way terminal block 4 poles IP68 H2O Stop, to be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

EAN	8054793833811
Mounting	Ground
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Number of lamps	1
Power (W)	8
Source flux (lm)	816
System flux (lm)	580

Physical

Color	Forest Green
Trim	No
Net weight (lb)	6.61
Gross weight (lb)	3.97
Package height (in)	34.45
Package width (in)	6.81
Package length (in)	6.5
Package volume (in)	1524.2
IP internal	65
H2O stop	No
Dynamic load (kg)	No

Download

Family spec sheet	ZIP
Mounting instructions	ZIP

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Light distribution	Symmetric
CCT (K)	3000
CRI>	80

Electrical

Insulation class	I
Frequency (Hz)	60
Main voltage (Vac)	120
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 1-10V
Dimming interface	Dimmer Integrated

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class D

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional

Accessories & Power Supply



OPTIONAL
Accessory

F003Z010000

Base plate with bolt