

FLOS

03.2008.14A Black

Bon Jour Ø 145

Designed by Philippe Starck, 2016



Recessed luminaire with LED light source. Remote 220/240V power supply included.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Semirecessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
System power (W)	36
Source flux (lm)	3840
Lumen Output (lm)	693

Physical

Colour	Black
Trim	Yes
Recessed depth (mm)	205
Bezel diameter (mm)	145
Net weight (kg)	1.11
Package volume (m3)	0.01
IP internal	20
IP external	44



Download

[Mounting instructions](#) PDF

Photometric Files

[LDT / IES](#) ZIP

Technical Drawings


[2D](#) ZIP

[3D](#) ZIP

[Bim](#) ZIP



Schematic light drawing



Beam Angle: 56°

h(m)	E(lx)	D(m)
1	969	1.05
2	242	2.11
3	108	3.16
4	61	4.22
5	39	5.27

Luminous flux luminaire
693 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	55
Beam angle C90-270 (°)	55
UGR _L	<16

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	110-240
LED current (mA)	900
Power supply	Remote included
Dimmable	No
Dimming interface	Remote Dimmable (Dimmer Not Included)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Notes

Pre-installation frame must be ordered separately

Accessories & Power Supply



REQUIRED
Frame

08.8975.00

Pre-installation frame



OPTIONAL
Filter

Optical

08.8977.00

Decorative screening accessory