

# FLOS

FA10017412 Opal

## C-Me Round 70 Rgb


Designed by FLOS Outdoor, 2008



LED source included. Remote electric power supply with DMX 3chx350mA interface, to be ordered separately. Requires a junction box to be ordered separately. The luminaire is equipped with a protruding, neoprene, 200 mm cable and a wiring kit with crimp connectors and adhesive heat-shrink tubing guaranteeing the water tightness of the connection. Extra clear transparent glass.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                      |
|------------------------|----------------------|
| EAN                    | 8054793604930        |
| Mounting               | In-ground            |
| Environments           | Outdoor wet location |
| Light source type      | LED                  |
| Light sources included | Yes                  |
| LED type               | Power LED            |
| Number of lamps        | 1                    |
| Power (W)              | 3                    |
| System power (W)       | 3.4                  |

### Physical


|                     |       |
|---------------------|-------|
| Colour              | Opal  |
| Orientation         | Fixed |
| Net weight (kg)     | 0.37  |
| Package height (mm) | 90    |
| Package width (mm)  | 140   |
| Package length (mm) | 140   |
| IP internal         | 67    |
| IP external         | 66    |

### Download

Mounting instructions



### Ecodesign and Energy Labelling



## Photometric

|                    |           |
|--------------------|-----------|
| Lighting type      | Direct    |
| Light distribution | Symmetric |
| CCT (K)            | RGB       |
| Extreme cut off    | No        |

## Electrical

|                    |   |
|--------------------|---|
| Insulation class   | III   |
| Frequency (Hz)     | 50/60                                       |
| Main voltage (Vac) | 24  |
| Power supply       | Remote excluded                             |
| Dimmable           | Yes   |
| Power supply type  | Dimmable DMX                                |
| Dimming interface  | Remote Dimmable<br>(Dimmer Not<br>Included) |
| Emergency          | No  |

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance'

Dimmable version on request

---

## Accessories & Power Supply



### REQUIRED Power supply

F990B22A000

Power supply with DMX interface for RGB fixtures 36W/220÷240v-3CH x 350mA (3CH x 10 x 1W) DMX control allowed IP67 Class I Selv Eq.



### REQUIRED Accessory

FA101

Box for Installation C-Me Round 70/90



### OPTIONAL Accessory

F990B10A000

DMX controller; dimmer switch for recessed box (60mm hole centres)



### OPTIONAL Accessory

F990B11A000

DMX controller; stand-alone/pc interface.



### OPTIONAL Accessory

F990B13A000

DMX splitter 512



### OPTIONAL Accessory

F990B12A000

DMX cable - shielded twisted pair with 110 Ohm constant impedance