

## C1 Double Spot Wall Large Ø 56


Designed by Vincent Van Duysen, 2020



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall surface        |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Power (W)              | 28                  |
| Source flux (lm)       | 2799                |
| System flux (lm)       | 2216                |

### Physical

|                          |            |
|--------------------------|------------|
| Color                    | Anthracite |
| Orientation              | Adjustable |
| Rotation (°)             | 180        |
| Longitudinal tilting (°) | 60         |
| IP internal              | 20         |

### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">PDF</a> |

### Photometric Files

|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
|-----------|---------------------|

### Technical Drawings


|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |



### Ecodesign and Energy Labelling



Schematic light drawing



Photometric

|                          |                              |
|--------------------------|------------------------------|
| Lighting type            | Direct, Indirect             |
| Light distribution       | Symmetric                    |
| CCT (K)                  | 3000                         |
| CRI>                     | 90                           |
| Rf fidelity index        | 91                           |
| Rg gamut index           | 98                           |
| LED Life / Failure Ratio | L80B20 >36.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 45                           |
| Beam angle C90-270 (°)   | 45                           |
| Extreme cut off          | No                           |


Electrical

|                  |                 |
|------------------|-----------------|
| Insulation class | III             |
| LED current (mA) | 950-1200        |
| Driver           | Remote excluded |
| Dimmable         | Yes             |

Notes

Photometric data without up diffuser.

Accessories & Power Supply




REQUIRED  
Accessory

Installation

08.0226.00A9S

C1 Wall Large Double No Trim  
Installation Frame




REQUIRED  
Power supply

Electrical

SP40W1200MA-10V-A01

Splice Box 40W, 1% dim, 0-10V,  
1200mA 120/277V.



REQUIRED  
Accessory

Installation

08.0254.00A9S

C1 Wall Large Double Surface  
Flush accessory