

## C1 Double Spot Wall Small Ø 35


Designed by Vincent Van Duysen, 2020



Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall surface        |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 12                  |
| System flux (lm)       | 745                 |

### Physical

|                          |             |
|--------------------------|-------------|
| Color                    | Matte White |
| Orientation              | Adjustable  |
| Rotation (°)             | 180         |
| Longitudinal tilting (°) | 60          |
| IP internal              | 20          |
| IP external              | 20          |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                        |                  |
|------------------------|------------------|
| Lighting type          | Direct, Indirect |
| Light distribution     | Symmetric        |
| CCT (K)                | 2700             |
| CRI>                   | 90               |
| Beam angle C0-180 (°)  | 18               |
| Beam angle C90-270 (°) | 18               |
| Extreme cut off        | No               |
| UGR <sub>L</sub>       | <10              |

Electrical

|                  |                 |
|------------------|-----------------|
| Insulation class | III             |
| LED current (mA) | 500             |
| Driver           | Remote excluded |
| Dimmable         | Yes             |
| Emergency type   | No              |

Notes

Photometric data without up diffuser.

Accessories & Power Supply



REQUIRED  
Accessory

Installation


08.0228.DR.9S  
C1 Wall Small Double Surface  
Mounted Canopy



REQUIRED  
Accessory

Installation

08.0228.ES.9S  
C1 Wall Small Double Surface  
mounted canopy



REQUIRED  
Power supply

Electrical


SP20W500MA-PEQ-S01  
Lutron EcoSystem Splice Box  
20W, 1% dim, listed driver with  
enclosure,500mA, 120/277V.



REQUIRED  
Accessory

Installation

08.0228.DY.9S  
C1 Wall Small Double Surface  
Mounted Canopy



REQUIRED  
Power supply

Electrical

SP40W500MA-10V-A02  
Splice Box 40W, 1% dim, 0-10V,  
500mA 120/277V.



REQUIRED  
Accessory

Installation

08.0227.00.9S  
C1 Wall Small Double No Trim  
Installation Frame