

# FLOS

03.1220.ES Brushed Bronze

## C1 Mono Spot Ceiling Small Ø 35

Designed by Vincent Van Duysen, 2021




LED - Power LED - 6W - 376lm - 2700K - CRI> 90 - Beam° 15

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling surface     |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 6                   |
| System flux (lm)       | 376                 |

### Physical

|                          |                |
|--------------------------|----------------|
| Color                    | Brushed Bronze |
| Orientation              | Adjustable     |
| Rotation (°)             | 355            |
| Longitudinal tilting (°) | 60             |
| IP internal              | 20             |
| IP external              | 20             |

### Download

Family spec sheet [↓ ZIP](#)

Mounting instructions [↓ PDF](#)

### Photometric Files

LDT / IES [↓ ZIP](#)


### Technical Drawings

2D [↓ ZIP](#)

3D [↓ ZIP](#)



## Schematic light drawing



### Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 2700      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 15        |
| Beam angle C90-270 (°) | 15        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

### Electrical

|                  |                 |
|------------------|-----------------|
| Insulation class | III             |
| LED current (mA) | 500             |
| Driver           | Remote excluded |
| Dimmable         | Yes             |
| Emergency type   | No              |

## Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.0211.DY.9S

C1 Ceiling Small Surface Mounted  
Canopy




REQUIRED  
Accessory

Installation

08.0211.ES.9S

C1 Ceiling Small Surface mounted  
canopy



REQUIRED  
Power supply

Electrical

SP20W500MA-PEQ-S01

Lutron EcoSystem Splice Box  
20W, 1% dim, listed driver with  
enclosure, 500mA, 120/277V.




REQUIRED  
Accessory

Installation

08.0211.ER.9S

C1 Ceiling Small Surface mounted  
canopy



REQUIRED  
Power supply

Electrical

SP40W500MA-10V-A02

Splice Box 40W, 1% dim, 0-10V,  
500mA 120/277V.



Ø 3.23"  
⚡

REQUIRED  
Accessory

Installation

08.0208.00.9S

C1 Ceiling Small No Trim  
Installation Frame.