

FLOS

03.1225.ER Brushed Steel

C1 Mono Spot Ceiling Small Ø 35

Designed by Vincent Van Duysen, 2021




LED - Power LED - 6W - 382lm - 3000K - CRI> 90 - Beam° 15

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Power (W)	6
System flux (lm)	382

Physical

Color	Brushed Steel
Orientation	Adjustable
Rotation (°)	355
Longitudinal tilting (°)	60
IP internal	20
IP external	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing




Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15
Extreme cut off	No
UGR _L	<10

Electrical

Insulation class	III
LED current (mA)	500
Driver	Remote excluded
Dimmable	Yes
Emergency type	No

Accessories & Power Supply



REQUIRED
Power supply

Electrical

SP40W500MA-10V-A02
Splice Box 40W, 1% dim, 0-10V,
500mA 120/277V.



REQUIRED
Accessory

Installation

08.0208.00.9S
C1 Ceiling Small No Trim
Installation Frame.



REQUIRED
Accessory

Installation

08.0211.DY.9S
C1 Ceiling Small Surface Mounted
Canopy



REQUIRED
Accessory

Installation


08.0211.ER.9S
C1 Ceiling Small Surface mounted
canopy



REQUIRED
Accessory

Installation

08.0211.ES.9S
C1 Ceiling Small Surface mounted
canopy



REQUIRED
Power supply

Electrical

SP20W500MA-PEQ-S01
Lutron EcoSystem Splice Box
20W, 1% dim, listed driver with
enclosure,500mA, 120/277V.