

FLOS

03.1225.ES Brushed Bronze

C1 Mono Spot Ceiling Small Ø 35

Designed by Vincent Van Duysen, 2021




LED - Power LED - 6W - 382lm - 3000K - CRI> 90 - Beam° 15

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

| | |
|------------------------|---------------------|
| Mounting | Ceiling surface |
| Environments | Indoor dry location |
| Light source type | LED |
| Light sources included | Yes |
| LED type | Power LED |
| Lamp category | LED |
| Power (W) | 6 |
| Lumen Output (lm) | 382 |

Physical

| | |
|--------------------------|----------------|
| Colour | Brushed Bronze |
| Orientation | Adjustable |
| Rotation (°) | 355 |
| Longitudinal tilting (°) | 60 |
| Spot diameter (mm) | 35 |
| Net weight (kg) | 0.18 |
| IP internal | 20 |
| IP external | 20 |

Download

[Mounting instructions](#)  PDF

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Photometric

| | |
|------------------------|-----------|
| Lighting type | Direct |
| Light distribution | Symmetric |
| CCT (K) | 3000 |
| CRI> | 90 |
| Beam angle C0-180 (°) | 15 |
| Beam angle C90-270 (°) | 15 |
| Extreme cut off | No |
| UGR _L | <10 |

Electrical

| | |
|------------------|-----------------|
| Insulation class | III |
| LED current (mA) | 500 |
| Power supply | Remote excluded |
| Dimmable | Yes |
| Emergency | No |

Accessories & Power Supply



REQUIRED
Power supply

Electrical

60.9207

Casambi continuous current power supply, dimmable
220/240V - 50/60Hz, 300mA -
16W / 350mA - 18,5W / 400mA -
21,5W / 450 mA - 24W / 500mA -
27W / 600mA - 32W / 650 mA -
35W / 700 mA - 36W /750 /800
/900 /1000 /1050 /1200 mA -
38W.



REQUIRED
Power supply

Electrical

60.9592

Non dimmable continuous current power supply. 15-30W,
220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.



ø82



REQUIRED
Frame

08.0208.00

No Trim installation frame for ceiling mounting



REQUIRED
Accessory

08.0211.DR

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Power supply

Electrical

60.7678

Continuous current supply source of 240V - 50/60Hz with dimmable Dali 2, Push dimming. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 500mA - 26W / 600mA - 31.2W / 700mA - 36.4W / 750mA - 39W / 800mA - 41.6...



REQUIRED
Accessory

08.0211.DY

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.ER

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Accessory

08.0211.ES

Coated aluminum mount for surface installation (ceiling)



REQUIRED
Power supply

Electrical

60.9208

Continuous current power supply
of 13-20W - Dim 1-10V&Push -
110/240V - 50/60Hz with power
current selected through
adjustable