

# FLOS

03.1206.ER Brushed Steel

## C1 Mono Spot Wall Small Ø 35

Designed by Vincent Van Duysen, 2021




LED - Power LED - 6W - 374lm - 3000K - CRI> 90 - Beam° 18

Adjustable luminaire with LED for indoor use, suitable for wall installation. The body can be extracted from the installation surface for 60° orientation on the vertical axis and 180° on the horizontal axis. Integrated Full cut-off optical group. The remote power supply (not included) must be placed in an accessible location. The installation frame must be ordered separately.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Wall surface        |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | Power LED           |
| Lamp category          | LED                 |
| Power (W)              | 6                   |
| System flux (lm)       | 374                 |

### Physical

|                          |               |
|--------------------------|---------------|
| Color                    | Brushed Steel |
| Orientation              | Adjustable    |
| Rotation (°)             | 180           |
| Longitudinal tilting (°) | 60            |
| IP internal              | 20            |
| IP external              | 20            |

### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |

### Photometric Files


|           |     |
|-----------|-----|
| LDT / IES | ZIP |
|-----------|-----|

### Technical Drawings

|    |     |
|----|-----|
| 2D | ZIP |
| 3D | ZIP |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 3000      |
| CRI>                   | 90        |
| Beam angle C0-180 (°)  | 18        |
| Beam angle C90-270 (°) | 18        |
| Extreme cut off        | No        |
| UGR <sub>L</sub>       | <10       |

Electrical

|                  |                 |
|------------------|-----------------|
| Insulation class | III             |
| LED current (mA) | 500             |
| Driver           | Remote excluded |
| Dimmable         | Yes             |
| Emergency type   | No              |

Accessories & Power Supply



REQUIRED  
Accessory

Installation

08.0209.DR.9S  
C1 Wall Small Mono Surface  
Mounted Canopy



REQUIRED  
Accessory

Installation


08.0209.ER.9S  
C1 Wall Small Mono Surface  
Mounted Canopy



REQUIRED  
Accessory

Installation

08.0209.DY.9S  
C1 Wall Small Mono Surface  
Mounted Canopy



REQUIRED  
Power supply

Electrical


SP20W500MA-PEQ-S01  
Lutron EcoSystem Splice Box  
20W, 1% dim, listed driver with  
enclosure,500mA, 120/277V.



REQUIRED  
Accessory

Installation

08.0209.ES.9S  
C1 Wall Small Mono Surface  
Mounted Canopy



REQUIRED  
Power supply

Electrical


SP40W500MA-10V-A02  
Splice Box 40W, 1% dim, 0-10V,  
500mA 120/277V.



REQUIRED  
Accessory

Installation

08.0206.00.9S  
C1 Wall Small Mono No Trim  
Installation Frame



REQUIRED  
Accessory

Installation

08.0231.00.9S  
C1 Wall Small Mono Surface Flush  
accessory