

Camouflage 140 mm Anthracite

Designed by Piero Lissoni, 2016



8W - 579lm - 4000K - CRI> 80 - Beam° 157

Wall-mounted lamp emitting radial diffused light. Circular front panel in multiple stone finishes. Dissipating aluminum body with diffuser in transparent polycarbonate. Parabolic reflector in white polycarbonate. IP65-rated. 24V remote power supply to be ordered separately. Equipped with a 100 mm power cable. Version 110 V upon request.

Designed by Piero Lissoni, Camouflage blends architecture and light in a refined play of presence and absence. Switch off the light and, as if by magic, the lamp disappears. Switch it on and all you see is the glow: a subtle halo that enhances surfaces without revealing its source. A range of sophisticated stone finishes allows the design to blend in with the walls, giving the lamp its name, or stand out as an elegant accent.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

EAN	8054793585857
Mounting	Wall
Environments	Outdoor wet location
Light Source Type	LED
Light sources included	Yes
LED type	Top LED
Number of lamps	1
Power (W)	8
System power (W)	8
Source flux (lm)	960
System flux (lm)	579

Physical

Color	Anthracite
Orientation	Fixed
Length (in)	5.51
Net weight (lb)	1.13
Gross weight (lb)	1.26
Package height (in)	3.66
Package width (in)	7.8
Package length (in)	7.8
Package volume (in)	219.69
IP internal	65
Dynamic load (kg)	No

Download

Mounting instructions [ZIP](#)

Photometric Files


LDT / IES [ZIP](#)

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	157
Beam angle C90-270 (°)	157

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	24
Driver	Remote excluded
Dimming type	Non Dimmable, Dimmable DALI 1

Notes

We recommend using a connection system with a degree of protection greater than or equal to the degree of protection of the luminaire.

During the installation and the maintenance of the fixtures it is important to be careful and avoid damages on the paint coating.

Damages on the coating exposed to outdoor conditions or water, could cause corrosion.

Chemical substances affect the anticorrosion covering protection.

For LED fixtures, there is evidence that most of the damages are connected to electrical effects related to the insulations, which cause destructive electrical discharges

These effects are frequently caused by:

- over voltage coming from the mains' network where fixture is connected.
- electrostatic discharge (ESD) coming from the environment.

The use of a protective device against the overvoltage on the electrical installation is warmly suggest this helps to reduce the intensity of some of these phenomenon and prevent irreversible damages. The selection of the type of device to be used must be adjust on the electrical plant.
