

FLOS



F011A42F030.A Black/Black Lava

Captain Flint Outdoor H 1537 mm Black/Black Lava

Designed by Michael Anastassiades, 2017



8W - 744lm - 4000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

EAN	8054793212951
Mounting	Floor
Light source type	LED
Light sources included	Yes
LED type	LED array
Power (W)	8
System power (W)	8
Source flux (lm)	1221
Lumen Output (lm)	744


Physical

Colour	Black/Black Lava
Trim	No
Orientation	Adjustable
Transversal tilting (°)	270
Net weight (kg)	14.35
IP internal	65
Drive Over	No

Download

[Mounting instructions](#)  ZIP

Photometric Files

[LDT / IES](#)  ZIP

Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



Schematic light drawing



Beam Angle: 112°

h(m)	E(lx)	D(m)
1	263	2.95
2	66	5.91
3	29	8.86
4	16	11.81
5	11	14.76

Luminous flux luminaire
744 lm

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	4000
CRI>	80
Beam angle C0-180 (°)	110
Beam angle C90-270 (°)	110
Extreme cut off	No

Electrical

Insulation class	III
Frequency (Hz)	50/60
Main voltage (Vac)	220-240
Power supply	Remote included
Dimmable	Yes
Power supply type	Dimmable
Dimming interface	Switch Integrated (Remote Dimmable)
Emergency	No

Ecodesign and Energy

Labelling

