

# FLOS



F011A43F059.A Brass Finish/Grey Lava

## Captain Flint Outdoor H 1537 mm Brass Finish/Grey Lava

Designed by Michael Anastassiades, 2017



8W - 744lm - 4000K - CRI> 80 - Beam° 110

LED bulb included. 5-m cable with Schuko IP44 plug suitable for outdoor use. Backlit floor dimmer switch on the IP65 cable enables ON/OFF function and brightness regulation 30-100%. Casambi function on demand.

Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



### Main specifications

|                        |               |
|------------------------|---------------|
| EAN                    | 8054793213521 |
| Mounting               | Floor         |
| Light source type      | LED           |
| Light sources included | Yes           |
| LED type               | LED array     |
| Power (W)              | 8             |
| System power (W)       | 8             |
| Source flux (lm)       | 1221          |
| Lumen Output (lm)      | 744           |


### Physical

|                         |                        |
|-------------------------|------------------------|
| Colour                  | Brass Finish/Grey Lava |
| Trim                    | No                     |
| Orientation             | Adjustable             |
| Transversal tilting (°) | 270                    |
| Net weight (kg)         | 14.35                  |
| IP internal             | 65                     |
| Drive Over              | No                     |

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP

### Technical Drawings


[2D](#)  ZIP

[3D](#)  ZIP

[Bim](#)  ZIP



## Schematic light drawing



## Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| CCT (K)                | 4000      |
| CRI>                   | 80        |
| Beam angle C0-180 (°)  | 110       |
| Beam angle C90-270 (°) | 110       |
| Extreme cut off        | No        |

## Electrical

|                    |  |
|--------------------|--|
| Insulation class   | III                                    |
| Frequency (Hz)     | 50/60                                  |
| Main voltage (Vac) | 220-240                                |
| Power supply       | Remote included                        |
| Dimmable           | Yes                                    |
| Power supply type  | Dimmable                               |
| Dimming interface  | Switch Integrated<br>(Remote Dimmable) |
| Emergency          | No                                     |

## Ecodesign and Energy

### Labelling

