



F011A24FU55.A Brushed Stainless Steel/Occhio di Pernice

## Captain Flint Outdoor H 1537 mm Brushed Stainless Steel/Occhio di Pernice

Designed by Michael Anastassiades



613lm - Beam° 110

Outdoor floor lamp emitting direct light. Stem in painted steel or brushed brass with rotating cone and opal photoengraved polycarbonate diffuser. Weighted stone base. Backlit floor dimmer on IP65 cable allows on/off and 30–100% light adjustment. Casambi function available on request.

Designed by Michael Anastassiades, Captain Flint is a sleek and graceful design that embodies a sense of equilibrium, with the cone appearing to balance delicately on its point, creating a refined interplay between stability and movement. This outdoor bollard version is an evolution of the original indoor floor design.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                  |               |
|------------------|---------------|
| EAN              | 8054793210445 |
| Mounting         | Floor         |
| System flux (lm) | 613           |

### Physical

|                   |                                           |
|-------------------|-------------------------------------------|
| Color             | Brushed Stainless Steel/Occhio di Pernice |
| Orientation       | Adjustable                                |
| Net weight (lb)   | 31.64                                     |
| Gross weight (lb) | 31.86                                     |
| IP internal       | 65                                        |

### Download

|                       |                     |
|-----------------------|---------------------|
| Family spec sheet     | <a href="#">ZIP</a> |
| Mounting instructions | <a href="#">ZIP</a> |

### Photometric Files


|           |                     |
|-----------|---------------------|
| LDT / IES | <a href="#">ZIP</a> |
| LDT / IES | <a href="#">ZIP</a> |
| LDT / IES | <a href="#">ZIP</a> |

### Technical Drawings

|    |                     |
|----|---------------------|
| 2D | <a href="#">ZIP</a> |
| 3D | <a href="#">ZIP</a> |



Schematic light drawing



Photometric

|                        |           |
|------------------------|-----------|
| Lighting type          | Direct    |
| Light distribution     | Symmetric |
| Beam angle C0-180 (°)  | 110       |
| Beam angle C90-270 (°) | 110       |

Electrical

|                |       |
|----------------|-------|
| Frequency (Hz) | 50/60 |
|----------------|-------|