

FLOS

 FU185444 Anodized Champagne

COORDINATES S4 UL CHA

Designed by Michael Anastassiades, 2020

161W - 8830lm - 2700K - CRI> 95

Coordinates is a lighting system consisting of horizontal and vertical strip lights that form illuminated grid-like structures of various complexities. This collection of standard chandeliers of pared-down configurations that can be used in any setting. Each suspended element is powered and supported by an invisible electrical and mechanical connection designed specifically to allow for the composition of the four hanging models (S1, S2, S3, S4). The S Module is also available to create semi-custom designs for large-scale installations. Behind the design: This design evolved from a commission for the feature lighting of the main dining area of the historic Four Seasons restaurant in New York City. The restaurant relocated and opened in 2018 with the interiors designed by S˜o Paolo-based architect Isay Weinfeld.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

EAN	8059607034354
Mounting	Suspension
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED Module
Power (W)	161
System flux (lm)	8830

Physical

Color	Anodized Champagne
Length (in)	69.68
Cord color	Black
Canopy color	Anodized Champagne
Canopy height (in)	3.740
Net weight (lb)	17.42
Gross weight (lb)	31.97
Package volume (in)	3827.42
IP internal	20



Download

Mounting instructions  PDF

Photometric Files

ULD  ZIP

Technical Drawings

3D  ZIP



Photometric




Lighting type	Total
Light distribution	Asymmetric
CCT (K)	2700
CRI>	95
Extreme cut off	No

Electrical




Insulation class	I
Frequency (Hz)	50/60
Main voltage (Vac)	100-240
Driver	Integrated
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable 1-10V, Dimmable DALI 1, Dimmable Push
Dimming interface	Remote Dimmable (Dimmer Not Included)
Batteries inside	No

Ecodesign and Energy
Labelling

This product contains a light
source of energy efficiency
class F



Replaceable (LED only)
light source by a
professional



Replaceable control
gear by a professional

Accessories & Power Supply




OPTIONAL

RF27318

Push button and cables assembly
for dimmer

Spare Parts



- | | | |
|-----|---|-----------|
| 01. | Coordinates S Assembly Big Rose
Anodized Champagne | RF1873144 |
| 02. | Led dimmer kit | RF35452 |
| 03. | Coordinates Rod Assembly L1760
H-11 Anodized Champagne | RF30985 |
| 04. | Coordinates Rod Assembly L1760
H-10 Anodized Champagne | RF30984 |
| 05. | Coordinates Suspension 4 Rod
Assembly L920 S-14 Anodized
Champagne | RF30983 |
| 06. | Coordinates Suspension 4 Rod
Assembly L920 S-13 Champagne | RF30982 |
| 07. | Coordinates Suspension 4 Rod
Assembly L920 SA-50 Anodized
Champagne | RF30267 |



RF1873144
Coordinates S Assembly Big Rose
Anodized Champagne



RF35452
Led dimmer kit



RF30985
Coordinates Rod Assembly L1760
H-11 Anodized Champagne



RF30984
Coordinates Rod Assembly L1760
H-10 Anodized Champagne



RF30983
Coordinates Suspension 4 Rod
Assembly L920 S-14 Anodized
Champagne



RF30982
Coordinates Suspension 4 Rod
Assembly L920 S-13 Champagne



RF30267
Coordinates Suspension 4 Rod
Assembly L920 SA-50 Anodized
Champagne