

Data Connection Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2018




Length: 300 - Ceiling surface

Data connection rod rose ø140mm. Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Colour	Black
Trim	No
Length (mm)	300
Net weight (kg)	0.84
IP internal	20
IP external	20

Download

Mounting instructions



Electrical

Power supply	Remote excluded
Power supply type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1
Emergency	No

Notes

The closure terminals will also be electrified and must be ordered separately. Data connection rod rose $\varnothing 140$ mm: Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply
ACCESSORYTYPE1

60.8919
LED Power Supply Source for remote installation. 48V/320W. 100/240 Vac



REQUIRED
Power supply
ACCESSORYTYPE1

60.9170
LED power supply source for remote installation, 48V/120W. 220/240 Vac



REQUIRED
Power supply
ACCESSORYTYPE1

60.9607
LED power supply source for remote installation, 110Vac-150W / 220Vac-200W



REQUIRED
Component
06.5135.14A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible




REQUIRED
Component
06.5135.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.14A
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component
06.5142.40A
End Cap On board dimmer/FLOS Control® by Casambi compatible



OPTIONAL
Power supply
ACCESSORYTYPE1
08.0613.14A
Dimmable control box 1-10V, 24/48V. For remote installation.