

Data Connection Rod Rose Ø 140 mm

Designed by Vincent Van Duysen, 2018




Length: 15.75 - Ceiling surface

Data connection rod rose ø140mm. Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling surface
Environments	Indoor dry location
Light sources included	no

Physical

Color	White
Trim	No
Length (in)	15.75
IP internal	20
IP external	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF



Electrical

Driver	Remote excluded
Dimming type	Non Dimmable, Dimmable 1-10V, Dimmable DALI 1
Emergency type	No

Notes

The closure terminals will also be electrified and must be ordered separately. Data connection rod rose $\varnothing 140$ mm: Use one for each line of the installation, for connection to DALI or 1-10V signal source. Adjustable 25 mm, to adapt it to irregular ceilings.

Accessories & Power Supply



REQUIRED
Power supply

LEDSB96W48V-NDM-D01
LED Driver, 48VDC, 96W, Non-Dimming, 120-277V



REQUIRED
Power supply

LEDSB60W48V-NDM-D01
LED Driver, 48VDC, 60W, Non-Dimming, 120-277V



REQUIRED
Power supply

ACCESSORYTYPE1

LEDSB30W48V-NDM-D01
LED power supply source for remote installation, 48V/30W



REQUIRED
Component

06.5135.14A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible



REQUIRED
Component

06.5135.40A
End Cap Dali/1-10V/FLOS Control® by Casambi compatible




REQUIRED
Component

06.5142.14A
End Cap On board dimmer/FLOS Control® by Casambi compatible



REQUIRED
Component

06.5142.40A
End Cap On board dimmer/FLOS Control® by Casambi compatible



OPTIONAL
Power supply

ACCESSORYTYPE1

08.0613.14A
Dimmable control box 1-10V, 24/48V. For remote installation.