

# FLOS

FA53917233-300 Anthracite

## Dooku 400 Single Top Pole Ø102 mm Asymmetric Optic Dimmable Dali

Designed by FLOS Outdoor



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Fixing bracket included. Equipped with a 400mm protruding neoprene cable section and IP68 connectors. Smart-City version available upon request. Single socket for 102mm diameter post. The post must be ordered separately. Smart-City version available upon request.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

EAN	8054793807454
Mounting	Pole Top
Power (W)	67
Source flux (lm)	18252
Lumen Output (lm)	15010

### Physical

Colour	Anthracite
Orientation	Fixed
Net weight (kg)	13.08
Package height (mm)	605
Package width (mm)	175
Package length (mm)	150
Package volume (m <sup>3</sup> )	0.02
IP internal	65

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



Beam Angle: 62°

h(m)	E(lx)	D(m)
1	1040	2.30
2	260	4.60
3	116	6.90
4	65	9.20
5	42	11.50

## Photometric

Extreme cut off No

## Electrical

Power supply type Dimmable DALI 1

Emergency No

## Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance

---