

# FLOS

FA53909206-310 Grey

## Dooku 400 Single Top Pole Ø102 mm Street Optic Dimmable 1-10V

Designed by FLOS Outdoor



LED source included. Integrated power supply 220-240V ON/OFF and dimmable 1-10V or DALI. Fixing bracket included. Equipped with a 400mm protruding neoprene cable section and IP68 connectors. Smart-City version available upon request. Single socket for 102mm diameter post. The post must be ordered separately. Smart-City version available upon request.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

### Main specifications

|                   |               |
|-------------------|---------------|
| EAN               | 8054793804910 |
| Mounting          | Pole Top      |
| Power (W)         | 67            |
| Source flux (lm)  | 18252         |
| Lumen Output (lm) | 15010         |

### Physical

|                                  |       |
|----------------------------------|-------|
| Colour                           | Grey  |
| Orientation                      | Fixed |
| Net weight (kg)                  | 13.08 |
| Package height (mm)              | 605   |
| Package width (mm)               | 175   |
| Package length (mm)              | 150   |
| Package volume (m <sup>3</sup> ) | 0.02  |
| IP internal                      | 65    |

### Download

[Mounting instructions](#)  ZIP

### Photometric Files

[LDT / IES](#)  ZIP


### Technical Drawings

[2D](#)  ZIP

[3D](#)  ZIP



## Schematic light drawing



### Photometric

CCT (K) 2700

Extreme cut off No

### Electrical

Power supply type Dimmable 0-10V

Emergency No

### Notes

Please check with your referent person in our Front Office if a code modification is needed to meet the required certification compliance