

FLOS

05.7031.74 Black

Easy Kap Ø 105 Fixed EVO

Designed by FLOS Architectural, 2019

LED



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

Physical

Colour	Black
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	155
Spot diameter (mm)	111
Length (mm)	111
Net weight (kg)	0.23
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54



Download

Mounting instructions	PDF
Item information	JPG

Photometric Files

LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP
Bim	ZIP



Ecodesign and Energy Labelling



Photometric

Lighting type	Direct
Light distribution	Symmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240

Notes

Not suitable for lens accessories.

