

05.7040.B1 White

## Easy Kap Ø 105 Wall-Washer

Designed by FLOS Architectural, 2019

LED retrofit

Recessed 12V lamp luminaire. Remote transformer not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | Bulb                |
| Light sources included | no                  |
| Lamp category          | LED retrofit        |
| Lamp type              | QR-CBC 51           |
| Lamp holders           | GX5.3               |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | White |
| Trim                | Yes   |
| Orientation         | Fixed |
| Recessed depth (mm) | 125   |
| Spot diameter (mm)  | 111   |
| Length (mm)         | 111   |
| Net weight (kg)     | 0.21  |
| Package height (mm) | 190   |
| Package width (mm)  | 175   |
| Package length (mm) | 220   |
| IP internal         | 54    |



### Download

[Mounting instructions](#) [↓ PDF](#)

[Item information](#) [↓ JPG](#)

### Photometric Files

[LDT / IES](#) [↓ ZIP](#)

### Technical Drawings

[Bim](#) [↓ ZIP](#)



### Ecodesign and Energy Labelling

 Replaceable (LED only) light source by an end-user

 Replaceable control gear by a professional

Photometric

|                    |            |
|--------------------|------------|
| Lighting type      | Direct     |
| Light distribution | Asymmetric |

Electrical

|                     |                 |
|---------------------|-----------------|
| Insulation class    | II              |
| Forward voltage (V) | 12              |
| Power supply        | Remote excluded |

Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.