

FLOS

05.7041.74 Black

Easy Kap Ø 105 Wall-Washer

Designed by FLOS Architectural, 2019

LED



'Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED
Lamp type	PAR16
Lamp holders	GZ10
Number of lamps	1

Physical

Colour	Black
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	125
Spot diameter (mm)	111
Length (mm)	111
Net weight (kg)	0.21
Package height (mm)	190
Package width (mm)	175
Package length (mm)	220
IP internal	54



Download

Mounting instructions [Download PDF](#)

Item information [Download JPG](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Ecodesign and Energy Labelling

 Replaceable (LED only) light source by an end-user

Photometric

Lighting type	Direct
Light distribution	Asymmetric

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240