FLOS

05.7633.GLB9S Gold

Easy Kap Ø30 Adjustable Set of 4 spots Non-IC

Designed by FLOS Architectural, 2023

LED - Power LED - 4 x 2.5W - 4 x 206lm - 2700K - CRI> 90

NON-IC Ceiling Recessed Trimless Downlight. Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary. Class 2



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Light Source Type	LED
Light sources included	Yes
LED type	Power LED
Lamp category	LED
Number of lamps	4
Power (W)	2.5
System power (W)	4.3
Source flux (lm)	247
System flux (lm)	206
Efficacy (lm/W)	48

Physical

Color	Gold
Trim	Yes
Orientation	Adjustable
Longitudinal tilting (°)	17
Transversal tilting (°)	17
Length (in)	1.4
IP internal	20
IP external	54

Download

Family spec sheet ZIP

Mounting instructions PDF

Ecodesign and Energy Labelling



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

RG IEC 62471

GWT 850°

IP 54

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
206 lm

Beam Angle: 50°

h(m)	E(lx)	D(m)
1	316	0.93
2	79	1.86
3	35	2.79
4	20	3.72
5	13	4.64

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
Rf fidelity index	89
Rg gamut index	101
LED Life / Failure Ratio	L90B50>51.000h_Tc85ºC
Extreme cut off	No
UGRL	<16

Electrical

Forward voltage (V)	3.3
LED current (mA)	800
Driver	Remote excluded
Dimming type	Non Dimmable, Mains Cut Dimming, Dimmable DALI 2, Dimmable 1-10V
Dimming interface	Remote Dimmable (Dimmer Not Included)

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply



REQUIRED
Power supply

ACCESSORYTYPE1

LEDSB40W800MA-V-Y1

LED DVR Variable Dim Triac, ELV, 40W, 800mA ,120/277V.



REQUIRED
Power supply

ACCESSORYTYPE1

SP12W850MA-DAL-T01

Splice Box UL 7″x3-5/8″x1-1/4″, With Eldoled Eco Drive Driver Programmed to 850mA,12WDALI Dimmable, 120-277V.



REQUIRED
Power supply

ACCESSORYTYPE1

SP12W850MA-10V-T01

Splice Box UL 7″x3-5/8″x1-1/4″, With Eldoled Eco Drive Driver Programmed to 850mA, 12W, 0-10V Dimmable, 120-277V.

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.