

05.7212.B1.9S White

Easy Kap Ø 50 Adjustable Optic Flood

Designed by FLOS Architectural, 2019

LED - LED array - 7.3W - 496lm - 2700K - CRI> 90 - Beam° 49

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	7.3
System power (W)	8.6
Source flux (lm)	670
System flux (lm)	496
Efficacy (lm/W)	57

Physical

Color	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Spot diameter (in)	2.3299999999999996
Net weight (lb)	0
IP internal	20
IP external	54



Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	---------------------

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Ecodesign and Energy Labelling

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional


Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L80B50>50.000h (Tc=85°C)
Beam angle C0-180 (°)	49
Beam angle C90-270 (°)	49
Extreme cut off	No
UGRL	<19

Electrical

Insulation class	III
Frequency (Hz)	0
Forward voltage (V)	35.9
LED current (mA)	200
Driver	Remote excluded
Dimmable	Yes
Dimming type	Dimmable 0-10V, Dimmable DALI 2, Dimmable ELV, Dimmable Push

Accessories & Power Supply



REQUIRED
Power supply

ACCESSORYTYPE1

SP10W200MA-DAL-Y1
Splice Box UL DALI & PUSH
Dimmable 200mA LED Driver
10W Size: 7" x 2.2" x 1.2"

REQUIRED
Power supply

ACCESSORYTYPE1

SP10W200MA-VAR-Y1
Splice Box UL TRIAC & 0-10V
Dimmable 200mA LED Driver
10W Size: 7" x 2.2" x 1.2"