FLOS

03.4153.B1.UQ White

Easy Kap Ø 80 Adjustable Optic Spot - Non IC

Designed by FLOS Architectural, 2017

9.2W - 704lm - 2700K - CRI> 90 - Beam° 18

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	908
System flux (lm)	704
Efficacy (lm/W)	76

Physical

Color	White
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Net weight (lb)	7.77
Gross weight (lb)	9.15
IP internal	54

Download

Family spec sheet ZIP

Mounting instructions PDF

Photometric Files

LDT / IES ZIP

RG IEC 62471

GWT 850°

IP 54

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Schematic light drawing



Luminous flux luminaire
704 lm (EXTREME CUT OFF)

Beam Angle: 18°

h(m)	E(lx)	D(m)
1	2811	0.33
2	703	0.66
3	312	0.99
4	176	1.33
5	112	1.66

Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	18

Electrical

Insulation class	III
Forward voltage (V)	18.2
LED current (mA)	500

Notes

Diffusing lens included

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.

Accessories & Power Supply



REQUIRED
Power supply

SP14W500MA-ELV-E01

Splice Box 9"x2"x1.5", 500mA , 14W, ELV Dimmable, Thermal 120V



REQUIRED
Power supply

SP20W500MA-120-V01

Splice Box9"x2"x1.5", 500mA , 20W, 0-10V , Dimmable, Thermal 120V



REQUIRED
Power supply

ACCESSORYTYPE1

SP20W500MA-277-V01

Splice Box 9” x 2” x 1.5”, 500mA, 20W, 0-10V, 277V



OPTIONAL
Housing and Hanger Bar

TRAY-0001

Registration Tray - non electrical, place holder for non IC new construction, Ø2.95"

©2026 Flos - P.IVA 00290820174 - 10/18/2026

In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warranty in any way.