


Easy Kap Ø 80 Fixed Optic Spot - Airtight IC Rated T24 JA8

Designed by FLOS Architectural, 2017

9.2W - 628lm - 2700K - CRI> 90 - Beam° 19

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	908
System flux (lm)	628
Efficacy (lm/W)	68

Physical

Color	Black
Trim	Yes
Orientation	Fixed
Spot diameter (in)	3.15
Net weight (lb)	0.53
Gross weight (lb)	0.62
Package volume (in)	62
IP internal	20
IP external	54

Download


[Family spec sheet](#) [ZIP](#)
[Mounting instructions](#) [PDF](#)

Photometric Files

[LDT / IES](#) [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	19
Beam angle C90-270 (°)	19
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	18.4
LED current (mA)	500
Driver	Remote excluded

Notes

Diffusing lens included

Accessories & Power Supply



REQUIRED
Housing and Hanger Bar

08.7060.00.90

Easy Kap 80 Round Airtight
Housing for New construction,
Integral 0-10V dimmable. driver.
Title 24 - JA8, CCEA Chicago
Plenum



REQUIRED
Housing and Hanger Bar

08.1201.00.UL

Bar Hanger Set , Male-Female (set
of 2)