



03.4287.GL.UQ Gold

## Easy Kap Ø 80 Fixed Optic Spot - Non IC

Designed by FLOS Architectural, 2017


9.2W - 712lm - 3000K - CRI> 90 - Beam° 19

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light Source Type      | LED                 |
| Light sources included | Yes                 |
| LED type               | LED array           |
| Number of lamps        | 1                   |
| Power (W)              | 9.2                 |
| Source flux (lm)       | 956                 |
| System flux (lm)       | 712                 |
| Efficacy (lm/W)        | 77                  |

### Physical

|                   |       |
|-------------------|-------|
| Color             | Gold  |
| Trim              | Yes   |
| Orientation       | Fixed |
| Net weight (lb)   | 7.77  |
| Gross weight (lb) | 9.15  |
| IP internal       | 54    |

### Download

Family spec sheet [ZIP](#)


Mounting instructions [PDF](#)

### Photometric Files

LDT / IES [ZIP](#)



Schematic light drawing



Photometric

|                          |                  |
|--------------------------|------------------|
| Lighting type            | Direct           |
| Light distribution       | Symmetric        |
| CCT (K)                  | 3000             |
| CRI>                     | 90               |
| McAdam steps (SDCM)      | 3                |
| LED Life / Failure Ratio | L90B10 > 50.000h |
| Beam angle C0-180 (°)    | 19               |
| Beam angle C90-270 (°)   | 19               |


Electrical

|                     |      |
|---------------------|------|
| Insulation class    | III  |
| Forward voltage (V) | 18.2 |
| LED current (mA)    | 500  |

Notes


Diffusing lens included

Accessories & Power Supply




REQUIRED  
Power supply

SP14W500MA-ELV-E01  
Splice Box 9"x2"x1.5", 500mA ,  
14W, ELV Dimmable, Thermal  
120V




REQUIRED  
Power supply

SP20W500MA-120-V01  
Splice Box9"x2"x1.5", 500mA ,  
20W, 0-10V , Dimmable, Thermal  
120V



REQUIRED  
Power supply

ACCESSORYTYPE1  
SP20W500MA-277-V01  
Splice Box 9" x 2" x 1.5", 500mA,  
20W, 0-10V, 277V



OPTIONAL  
Housing and Hanger Bar

TRAY-0001  
Registration Tray - non electrical,  
place holder for non IC new  
construction, Ø2.95"