

FLOS

03.4295.74.98 Black

Easy Kap 80 Square Adjustable Optic Flood - Airtight IC Rated T24 JA8

Designed by FLOS Architectural, 2017


9.2W - 668lm - 3000K - CRI> 90 - Beam° 55

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	668
Efficacy (lm/W)	72

Physical

Color	Black
Trim	Yes
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	20
Transversal tilting (°)	20
Spot diameter (in)	3.15
Net weight (lb)	0.53
Gross weight (lb)	0.62
Package volume (in)	62
IP internal	20
IP external	54

Download


Family spec sheet [↓ ZIP](#)
Mounting instructions [↓ PDF](#)

Photometric Files

LDT / IES [↓ ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	55
Beam angle C90-270 (°)	55
Extreme cut off	No

Electrical

Insulation class	III
Forward voltage (V)	18.4
LED current (mA)	500
Driver	Remote excluded

Notes

Diffusing lens included

Accessories & Power Supply



REQUIRED
Housing and Hanger Bar

08.7062.00.90

Easy Kap 80 Square Airtight
Housing for New construction,
Integral 0-10V dimmable. driver.
Title 24 - JA8, CCEA Chicago
Plenum



REQUIRED
Housing and Hanger Bar

08.1201.00.UL

Bar Hanger Set , Male-Female (set
of 2)