

FLOS

03.4208.74 Black

Easy Kap 80 Square Fixed

Designed by FLOS Architectural, 2016


LED retrofit

Recessed 12V lamp luminaire. Remote transformer not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Number of lamps	1

Physical

Colour	Black
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	130
Spot diameter (mm)	80
Length (mm)	80
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23

Download

Mounting instructions	↓ PDF
Item information	↓ JPG

Photometric Files

LDT / IES	↓ ZIP
-----------	-------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP
Bim	↓ ZIP



Photometric

Lighting type	Direct
Light distribution	Symmetric


Electrical

Insulation class	III
Forward voltage (V)	12
Power supply	Remote excluded


Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional