

FLOS

03.4176.74.UQ Black

Easy Kap 80 Square Fixed Optic Spot - Non IC

Designed by FLOS Architectural, 2017


9.2W - 696lm - 3000K - CRI> 90 - Beam° 17

Recessed luminaire with LED light source. Power supply not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	9.2
Source flux (lm)	956
System flux (lm)	696
Efficacy (lm/W)	75

Physical

Color	Black
Trim	Yes
Orientation	Fixed
Spot diameter (in)	3.15
Net weight (lb)	7.77
Gross weight (lb)	9.15
IP internal	54

Download

Family spec sheet [ZIP](#)


Mounting instructions [PDF](#)

Photometric Files

LDT / IES [ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	3
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	17
Beam angle C90-270 (°)	17

Electrical

Insulation class	III
Forward voltage (V)	18.2
LED current (mA)	500

Notes

Diffusing lens included

Accessories & Power Supply



REQUIRED
Power supply

SP14W500MA-ELV-E01
Splice Box 9"x2"x1.5", 500mA ,
14W, ELV Dimmable, Thermal
120V




REQUIRED
Power supply

SP20W500MA-120-V01
Splice Box9"x2"x1.5", 500mA ,
20W, 0-10V , Dimmable, Thermal
120V



REQUIRED
Power supply

ACCESSORYTYPE1
SP20W500MA-277-V01
Splice Box 9" x 2" x 1.5", 500mA,
20W, 0-10V, 277V



OPTIONAL
Housing and Hanger Bar

TRAY-0002
Registration Tray - non electrical,
place holder for non IC new
construction, Square, 2.95 x 2.95"