

03.4220.B1 White

Easy Kap Ø 80 Wall-Washer

Designed by FLOS Architectural, 2016


LED retrofit

Recessed 12V lamp luminaire. Remote transformer not included. Installation frame not necessary.



Are you a professional and your project needs consulting and support?

[BOOK AN APPOINTMENT](#)



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	QR-CBC 51
Lamp holders	GX5.3
Number of lamps	1

Physical

Colour	White
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	120
Spot diameter (mm)	80
Length (mm)	80
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23

Download

Mounting instructions	Download PDF
Item information	Download JPG

Photometric Files

LDT / IES	Download ZIP
-----------	------------------------------

Technical Drawings

2D	Download ZIP
3D	Download ZIP
Bim	Download ZIP



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric


Electrical

Insulation class	III
Forward voltage (V)	12
Power supply	Remote excluded


Notes

Not suitable for lens accessories. Check your lamp dimentions to match the product.

Ecodesign and Energy Labelling



Replaceable (LED only) light source by an end-user



Replaceable control gear by a professional