

# FLOS

03.4221.74 Black

## Easy Kap Ø 80 Wall-Washer

Designed by FLOS Architectural, 2016

LED retrofit - Beam° 20

Recessed luminaire with main voltage source. Installation frame not necessary.



Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|                        |                     |
|------------------------|---------------------|
| Mounting               | Ceiling recessed    |
| Environments           | Indoor dry location |
| Light source type      | Bulb                |
| Light sources included | no                  |
| Lamp category          | LED retrofit        |
| Lamp type              | PAR16               |
| Lamp holders           | GU10                |
| Number of lamps        | 1                   |

### Physical

|                     |       |
|---------------------|-------|
| Colour              | Black |
| Trim                | Yes   |
| Orientation         | Fixed |
| Recessed depth (mm) | 140   |
| Spot diameter (mm)  | 80    |
| Length (mm)         | 80    |
| Net weight (kg)     | 0.12  |
| Package height (mm) | 90    |
| Package width (mm)  | 140   |
| Package length (mm) | 105   |
| IP internal         | 20    |
| IP external         | 23    |



### Download

Mounting instructions [Download PDF](#)

Item information [Download JPG](#)

### Photometric Files

LDT / IES [Download ZIP](#)

### Technical Drawings

2D [Download ZIP](#)

3D [Download ZIP](#)

Bim [Download ZIP](#)



### Ecodesign and Energy Labelling



Replaceable (LED only)  
light source by an end-user

Photometric

|                          |                               |
|--------------------------|-------------------------------|
| Lighting type            | Indirect, Direct              |
| Light distribution       | Asymmetric                    |
| LED Life / Failure Ratio | L80B50 > 50.000h<br>(Tc=85°C) |
| Beam angle C0-180 (°)    | 20                            |
| Beam angle C90-270 (°)   | 20                            |

Electrical

|                    |         |
|--------------------|---------|
| Insulation class   | II      |
| Frequency (Hz)     | 50/60   |
| Main voltage (Vac) | 220-240 |

Notes

Not suitable for lens accessories.