

Easy Kap Ø 80 Wall-Washer

Designed by FLOS Architectural, 2016

LED retrofit - Beam° 18



Recessed luminaire with main voltage source. Installation frame not necessary.

Are you a professional and your project needs consulting and support?


[BOOK AN APPOINTMENT](#)

Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	Bulb
Light sources included	no
Lamp category	LED retrofit
Lamp type	PAR16
Lamp holders	GU10
Number of lamps	1

Physical

Colour	Gold
Trim	Yes
Orientation	Fixed
Recessed depth (mm)	140
Spot diameter (mm)	80
Length (mm)	80
Net weight (kg)	0.12
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20
IP external	23



Download

Mounting instructions	↓ PDF
Item information	↓ JPG

Photometric Files

LDT / IES	↓ ZIP
-----------	-----------------------

Technical Drawings

2D	↓ ZIP
3D	↓ ZIP
Bim	↓ ZIP



Ecodesign and Energy Labelling



Photometric

Lighting type	Indirect, Direct
Light distribution	Asymmetric
LED Life / Failure Ratio	L80B50 > 50.000h (Tc=85°C)
Beam angle C0-180 (°)	18
Beam angle C90-270 (°)	20

Electrical

Insulation class	II
Frequency (Hz)	50/60
Main voltage (Vac)	220-240

Notes

Not suitable for lens accessories.

