

Eclectic 70 Adjustable Flat

Designed by FLOS Architectural, 2022




7.5W - 444lm - 3000K - CRI> 90 - Beam° 14

Eclectic Ø70. Adjustable Downlight (35° tilt, 360° rotation). "Flat" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 55° cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light source type	LED
Light sources included	Yes
LED type	LED array
Number of lamps	1
Power (W)	7.5
System power (W)	9.9
Lumen Output (lm)	444
Efficacy (lm/W)	59

Physical

Colour	White
Orientation	Adjustable
Recessed depth (mm)	134
Spot diameter (mm)	75
Length (mm)	75
Net weight (kg)	0.16
Package height (mm)	90
Package width (mm)	140
Package length (mm)	105
IP internal	20

Download

Mounting instructions [Download PDF](#)

Photometric Files

LDT / IES [Download ZIP](#)

Technical Drawings


2D [Download ZIP](#)

3D [Download ZIP](#)

[Bim](#) [Download ZIP](#)



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	3000
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	92
Rg gamut index	98
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	14
Beam angle C90-270 (°)	14
UGRL	<10

Electrical

Insulation class	III
LED current (mA)	600
Power supply	Remote
Dimmable	Yes
Power supply type	Dimmable Casambi, Mains Cut Dimming, Dimmable 0-10V, Dimmable DALI 2, Dimmable 1-10V, Dimmable Push

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class E

Replaceable (LED only) light source by a professional

Replaceable control gear by a professional



REQUIRED
Power supply

ACCESSORYTYPE1

60.9162

Continuous current power supply 220/240V - 50/60Hz. Adjustable Current 300mA-13W / 350mA-15W / 400mA-18W / 450mA-20W / 500mA-22W / 550mA-24W / 600mA-27W / 650mA-29W / 700mA-31W / 750mA-32W / 800mA-33W / 850mA-35W / 900mA-38W / 950mA-40W / 1000/1050mA-4...



REQUIRED
Power supply

ACCESSORYTYPE1

60.7678

Continuous current supply source of 240V - 50/60Hz with dimmable Dali 2, Push dimming. 150mA - 7.8W / 200mA - 10.4W / 250mA - 13W / 300mA - 15.6W / 350mA - 18.2W / 400mA - 20.8W / 500mA - 26W / 600mA - 31.2W / 700mA - 36.4W / 750mA - 39W / 800mA - 41.6...



REQUIRED
Power supply

ACCESSORYTYPE1

60.9467

Mains dimming 20W Constant current power supply, AC phase-cut adjustable, trailing & leading edge dimming, 220/240V - 50/60Hz, with dip-switch programmable power supply current. Output current: 900mA - 20W / 850mA - 20W / 800mA - 20W / 750mA - 20W / 70...



REQUIRED
Power supply

ACCESSORYTYPE1

60.9592

Non dimmable continuous current power supply. 15-30W, 220/240V -50/60Hz with power current selected through adjustable switch. 350mA - 15W / 400mA - 17W / 450mA - 19W / 500mA - 22W / 550mA - 24W / 600mA - 26W / 650mA - 28W / 700mA - 30W.



REQUIRED
Power supply

ACCESSORYTYPE1

60.9208

Continuous current power supply of 13-20W - Dim 1-10V&Push - 110/240V - 50/60Hz with power current selected through adjustable



REQUIRED
Power supply

ACCESSORYTYPE1

60.9845

Continuous current power supply 40W, 220/240V - 50/60Hz with power current selected through adjustable switch. Dimmable 0-10V/PWM/RX. Output current: 1050mA - 40W / 1000mA - 40W / 950mA - 40W / 900mA - 37W / 850mA - 35W / 800mA - 33W / 750mA - 31W / 70...



REQUIRED
Power supply

ACCESSORYTYPE1

60.7785

Constant current power supply 42W, 220-240V CASAMBI dimmable.



REQUIRED
Frame

ACCESSORYTYPE2

08.0670.14

Trim Frame



REQUIRED
Frame

ACCESSORYTYPE2

08.0670.40

Trim Frame



REQUIRED
Frame

ACCESSORYTYPE2

08.0672.00

No Trim Frame




REQUIRED
Power supply

ACCESSORYTYPE1

60.9713.0600

600mA, 20 W, 220/240 V - 50/60
Hz constant current power
supply. Dimmable by Dali2



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0727.00

Honeycomb for Eclectic 70



OPTIONAL
Accessory

ACCESSORYTYPE2

08.0729.00

IP54 Lens for Eclectic 70
Adjustable



OPTIONAL
Filter

ACCESSORYTYPE4

08.0731.00

Colour Temperature Increaser for
Eclectic 70




OPTIONAL
Filter

ACCESSORYTYPE4

08.0732.00

Colour Temperature Decreaser
for Eclectic 70

Spare Parts



.	Spot Lens for Eclectic 70	08.0711.00
.	Medium Lens for Eclectic 70	08.0712.00
.	Flood Lens for Eclectic 70	08.0713.00
.	Cone Frontal for Eclectic 70	08.0721.14
.	Cone Frontal for Eclectic 70	08.0721.40
.	Soft Frontal for Eclectic 70	08.0722.14
.	Soft Frontal for Eclectic 70	08.0722.40
.	Flat Frontal for Eclectic 70	08.0723.14
.	Flat Frontal for Eclectic 70	08.0723.40
.	Module Fix for Eclectic 70	08.0739.00
.	Module Adjustable for Eclectic 70	08.0740.00



08.0711.00

Spot Lens for Eclectic 70



08.0712.00

Medium Lens for Eclectic 70



08.0713.00

Flood Lens for Eclectic 70



08.0721.14

Cone Frontal for Eclectic 70



08.0721.40

Cone Frontal for Eclectic 70



08.0722.14

Soft Frontal for Eclectic 70



08.0722.40

Soft Frontal for Eclectic 70



08.0723.14

Flat Frontal for Eclectic 70



08.0723.40

Flat Frontal for Eclectic 70



08.0739.00

Module Fix for Eclectic 70



08.0740.00

Module Adjustable for Eclectic 70