

FLOS

05.8023.40.UQ White

Eclectic 70 Adjustable Soft - Non IC

Designed by FLOS Architectural, 2022





LED - LED array - 7.5W - 408lm - 2700K - CRI> 90 - Beam° 15

Eclectic Ø70. Adjustable Downlight (35° tilt, 360° rotation). "Soft" style façade. Necessary installation pre-frames, not included (to be ordered separately). Recessed position of the LED: 47° cut-off angle. IP20 water tightness (for IP54, please ask the dedicated accessory). Alternative options for lenses, orientation modules and style façades are available as spare parts.

Are you a professional and your project needs consulting and support?

BOOK AN APPOINTMENT



Main specifications

Mounting	Ceiling recessed
Environments	Indoor dry location
Light Source Type	LED
Light sources included	Yes
LED type	LED array
Lamp category	LED
Number of lamps	1
Power (W)	7.5
System flux (lm)	408

Physical

Color	White
Orientation	Adjustable
Rotation (°)	360
Longitudinal tilting (°)	35
Transversal tilting (°)	35
Recessed depth (in)	5.27
Net weight (lb)	0.36
Gross weight (lb)	0.49
Package volume (in)	61.02
IP internal	20

Download

Family spec sheet	ZIP
Mounting instructions	PDF

Photometric Files


LDT / IES	ZIP
-----------	-----

Technical Drawings

2D	ZIP
3D	ZIP



Schematic light drawing



Photometric

Lighting type	Direct
Light distribution	Symmetric
CCT (K)	2700
CRI>	90
McAdam steps (SDCM)	2
Rf fidelity index	88
Rg gamut index	94
LED Life / Failure Ratio	L90B10 > 50.000h
Beam angle C0-180 (°)	15
Beam angle C90-270 (°)	15

Electrical

Insulation class	II
Forward voltage (V)	12.3
LED current (mA)	600
Driver	Attached Splice Box

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G

Replaceable (LED only) light source by an end-user

Replaceable control gear by a professional

Accessories & Power Supply



REQUIRED
Frame

ACCESSORYTYPE2

08.0670.14

Trim Frame



REQUIRED
Frame

ACCESSORYTYPE2

08.0670.40

Trim Frame




REQUIRED
Frame

ACCESSORYTYPE2

08.0672.00

No Trim Frame



REQUIRED

06.0399.00.90

Splice Box 600mA 1-10V for
Eclectic 70&90




OPTIONAL
Accessory

ACCESSORYTYPE2

08.0729.00

IP54 Lens for Eclectic 70
Adjustable



OPTIONAL
Accessory

ACCESSORYTYPE4

08.0727.00

Honeycomb for Eclectic 70



OPTIONAL
Filter

ACCESSORYTYPE4

08.0731.00

Colour Temperature Increaser for
Eclectic 70



OPTIONAL
Filter

ACCESSORYTYPE4

08.0732.00

Colour Temperature Decreaser
for Eclectic 70

Spare Parts



.	Spot Lens for Eclectic 70	08.0711.00
.	Medium Lens for Eclectic 70	08.0712.00
.	Flood Lens for Eclectic 70	08.0713.00
.	Cone Frontal for Eclectic 70	08.0721.14
.	Cone Frontal for Eclectic 70	08.0721.40
.	Soft Frontal for Eclectic 70	08.0722.14
.	Soft Frontal for Eclectic 70	08.0722.40
.	Flat Frontal for Eclectic 70	08.0723.14
.	Flat Frontal for Eclectic 70	08.0723.40
.	Module Fix for Eclectic 70	08.0739.00
.	Module Adjustable for Eclectic 70	08.0740.00



08.0711.00

Spot Lens for Eclectic 70



08.0712.00

Medium Lens for Eclectic 70



08.0713.00

Flood Lens for Eclectic 70



08.0721.14

Cone Frontal for Eclectic 70



08.0721.40

Cone Frontal for Eclectic 70



08.0722.14

Soft Frontal for Eclectic 70



08.0722.40

Soft Frontal for Eclectic 70



08.0723.14

Flat Frontal for Eclectic 70



08.0723.40

Flat Frontal for Eclectic 70



08.0739.00

Module Fix for Eclectic 70



08.0740.00

Module Adjustable for Eclectic 70