

Electrical DATA suspended Rod 27.56" (700mm)

Length: 27.56 - Suspension



Aircraft cable with mounting hardware 33ft (10m). Feed wire 37.8ft (11.5m)

Are you a professional and your project needs consulting and support?


BOOK AN APPOINTMENT

### Main specifications

|              |                     |
|--------------|---------------------|
| Mounting     | Suspension          |
| Environments | Indoor dry location |

### Physical

|                     |       |
|---------------------|-------|
| Color               | White |
| Length (in)         | 27.56 |
| Net weight (lb)     | 1.65  |
| Gross weight (lb)   | 2.16  |
| Package volume (in) | 2380  |
| IP internal         | 20    |



### Download

|                       |     |
|-----------------------|-----|
| Family spec sheet     | ZIP |
| Mounting instructions | PDF |



### Electrical

|        |        |
|--------|--------|
| Driver | Remote |
|--------|--------|

Accessories & Power Supply



REQUIRED  
Component

06.5135.14A

End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5135.40A

End Cap Dali/1-10V/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5142.14A

End Cap On board dimmer/FLOS  
Control® by Casambi compatible



REQUIRED  
Component

06.5142.40A

End Cap On board dimmer/FLOS  
Control® by Casambi compatible



REQUIRED  
Power supply

LEDSB60W48V-NDM-D01

LED Driver, 48VDC, 60W, Non-Dimming, 120-277V




REQUIRED  
Power supply

ACCESSORYTYPE1

LEDSB30W48V-NDM-D01

LED power supply source for  
remote installation, 48V/30W



OPTIONAL  
Power supply

ACCESSORYTYPE1

08.0613.14A

Dimmable control box 1-10V,  
24/48V. For remote installation.